



Océ VarioStream 8000 Single

24/7 Productivity



Fast and on the ball

You have to move quickly to keep up with the demands of new customers and ever-changing market trends. And so does your printing equipment – you need technology that's proven for ultimate reliability and yet state-of-the-art and infinitely flexible.

The Océ VarioStream® 8000 is engineered for maximum performance today and growth tomorrow. It handles high speed, high quality transaction-oriented applications and exacting Graphics Arts application with equal ease. Let your documents communicate more effectively by adding highlight color. Océ's unique Enhanced Print Quality feature and Océ CustomTone® color make the Océ VarioStream 8000 a true all-round athlete.

Perfect quality

The Océ VarioStream 8000 brings you extraordinary speed and accuracy. New ZG4 LED imaging and Super Cell technology that allows printing of 256 gray levels combine with excellent toner transfer to give you crisp graphics quality for your images, texts or graphics.

Extend your scope

Whether transactional or Graphic Arts applications, the Océ VarioStream 8000 is made to outperform. It offers matchless field-upgradable speeds – from 500 to 707 ppm in A4 Portrait (2-up) and from 530 to 750 ppm in US Letter Portrait (2-up). Its wide 19.5 inch path, pinless and pinfeed paper applications and the huge range of substrates it supports make it the printer of choice for a huge range of jobs.

Unrivalled upgradeability

The Océ VarioStream 8000 systems have a modular design that can easily and economically be extended at any time. They can be run as a duplex or triplex printing systems by adding print engines. Plug in the Océ Quick Change Developer Station for Océ CustomTone or MICR printing. This enormous flexibility means you can decide with confidence – your investment is future-proof with every Océ VarioStream 8000.

Technology

Variants

- Océ VarioStream 8550
- Océ VarioStream 8650
- Océ VarioStream 8750

Print system

- Electrophotographic printing system
- LED imaging technology

Fusing method

Heat and pressure fusing

Standard features

- Touch-screen Graphical User Interface and mouse for ease of use
- Enhanced Print Quality for industry leading image quality and productivity
- Advanced pinless paper transport for forms with and without tractor holes
- Single Point of Operation for remote monitoring
- High quality printing with up to 256 gray levels using Super Cell technology
- Type 1 pre- and post-processing interface
- Quick Change Developer Station (QCDS) for quickly changing toner type
- Océ TonerSafe™ insures that the toner and the developer station match
- Speed switch to lower speeds for special applications and post-processing devices¹

Maximum Printing Speeds

	Océ VarioStream 8550	Océ VarioStream 8650	Océ VarioStream 8750
A4 Portrait (2-up)	500 ppm	600 ppm	707 ppm
US Letter Portrait (2-up)	530 ppm	636 ppm	750 ppm
Meters/minute	74.1 mpm	88.92 mpm	104.88 mpm
Feet/minute	243.1 fpm	291.7 fpm	344.1 fpm

Connectivity

Native printer codes

IPDS, PCL5e (free choice of first printer code)

Interfaces

- Standard: Gigabit Ethernet Copper
- Optional: Gigabit Ethernet Optic and ESCON

Connects to

- Océ PRISMA® production (AFP/IPDS, TIFF, PDF, PostScript, PCL, LCDS (Metacode), OLD, PPML)
- Océ PRISMAproduction Host, SPS
- z/OS
- InfoPrint Manager
- BS2000
- Pres
- GMC
- HP3000/9000

Options

- Dual Print Quality Kit for maximum quality flexibility¹
- Second printer code (IPDS or PCL5e)
- Up to two additional interfaces
- Additional Quick Change Developer Station (QCDS) for MICR or CustomTone® printing
- Océ CustomTone with custom color toners¹
- MICR printing¹
- Upgrade to Twin and Triplex systems¹
- UP3I support for improved productivity and process control

Océ VarioStream 8000 Single

Physical

Dimensions

- Length: 2630 mm (103.5 inches)
- Width: 1326 mm (52.2 inches)
- Height: 1619 mm (63.7 inches)

Weight

1215 kg (2675 lbs)

Production

Print resolution

- 240/300/600 dpi (auto-detection and switching)
- Production Quality (bill, invoices, statements) available for all variants
- Graphics Quality (manuals, print-on-demand) available for the Océ VarioStream 8550

Paper

- Single layer continuous forms with or without tractor feed margins, perforated, colored, or preprinted
- Form width: 165–495.3 mm (6.5–19.5 inches), fully variable
- Print width: 482.6 mm (19 inches)
- Form length: 76.2–711.2 mm (3–28 inches) in increments of 1/60 inch
- Paper weight: 50–120 gsm (36–49 gsm on Océ specified papers and configurations), weights outside these limits are subject to satisfactory test results
- Paper feed: Roll, stack, jumbo stack

¹ Please contact your local sales representative for details



Printing for
Professionals

For information and services, visit us at www.oce.com

© 2007 Océ. Illustrations and specifications do not necessarily apply to products and services offered in each local market.

Technical specifications are subject to change without prior notice. All other trademarks are the property of their respective owners.